

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

**Reference number of the
declaration of performance:** IN55255070

Unique identification code of the product-type: MC-DUR 1000 Parat 04

Intended use: Synthetic resin screed for internal uses according to EN 13813
Application by hand according to EN 1504-3

Manufacturer: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
46238 Bottrop

System of AVCP: System 4 (for internal uses)

Harmonised standard: EN 13813:2002
EN 1504-3:2005

Notified body: Institut für Massivbau und Baustofftechnologie
Universität Karlsruhe (TH)
Identification no: 0754

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Efl ^{a)}	EN 13813:2002
Release of corrosive substances	SR	
Wear resistance	AR1	
Bond strength	B1,5	
Impact resistance	IR20	

¹⁾ The value in brackets is the lowest accepted value of any reading

Essential characteristic	Performance	Harmonised technical specification
Compressive strength	≥ 45 MPa	EN 1504-3:2005
Abrasion resistance	≥ 2,0 MPa	
Shrinkage	≥ 2,0 MPa	
Reaction to fire	Efl ^{a)}	


a) According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/Efl without further testing

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Hans-Günter Seltmann
Head of research and development and quality control

Bottrop, 19.12.2016
(place and date of issue)


.....
(signature)



Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.