Declaration of Performance



MC-Floor TopSpeed ESD

Reference number of the Declaration of Performance: IN5480070

| 1. | Unique ID code of the product type | MC-Floor TopSpeed ESD | |
|----|------------------------------------|---|--|
| 2. | Application(s) | Surface protection products – Coating | |
| | | Protection against ingress (1.3) | |
| | | Moisture control (2.2) | |
| | | Physical resistance (5.1) | |
| 3. | Manufacturer | MC-Bauchemie Müller GmbH & Co. KG | |
| | | Am Kruppwald 1-8 | |
| | | 46238 Bottrop / Germany | |
| 4. | Authorized representative | - | |
| 5. | System of AVCP | System 2+ (for uses in buildings and civil engineering works) | |
| 6. | Harmonised standard | EN 1504-2: 2004 | |
| 7. | Notified body | Institut für Massivbau und Baustofftechnologie | |
| | • | Universität Karlsruhe (TH) | |
| | | ID code 0754 | |

8. Declared performances

| Essential characteristic | Performance | harmonised technical specification | |
|---|---|------------------------------------|--|
| Linear shrinkage | ≤ 0,3% | | |
| Coefficient of thermal expansion | Rigid systems for outdoor use: αT ≤ 30 × 106 K1 | EN 1504-2: 2004 | |
| Wear resistance | < 3000 mg | | |
| Cross-cut test to determine adhesive strength | ≤ GT2 | | |
| CO2 permeability | sD > 50 m | | |
| Water vapour permeability | Class I sD < 5 m Class II 5 m \leq sD \leq 50 m Class III sD > 50 m | | |
| Capillary water absorption | < 0,1 kg/m-²h-0,5 | | |
| Freeze-thaw cycling with de-icing salt attack | No blisters, no cracks, no spalling | | |
| Ageing: 7 days at 70 °C | Rigid systems without traffic load: ≥ 1.0 (0.7) | | |
| Resistance to thermal shock | Rigid systems with traffic load: ≥ 2.0 (1.5) | | |
| Resistance to chemicals | No visible defects | | |
| Resistance to strong chemical attack | Reduction in hardness of less than 50% | | |
| Impact strength | Class I: ≥ 4 Nm Class II: ≥ 10 Nm Class III: ≥ 20 Nm | | |
| Hazardous substances | EN 1504-2, Pkt. 5.3 | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

van Diemen Head of research and development and quality control



Bottrop, 28.05.2021 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.