

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

**Reference number of the
declaration of performance:** IN 5203000

**Unique identification code of
the product-type:** MC-Injekt 1264 TF (P)

Intended use: Concrete injection for force transmitting filling of cracks,
voids and interstices (F)
U (F1) W (1) (1) (5/35) (1)

Manufacturer: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
46238 Bottrop

System of AVCP: System 2+
(for uses in buildings and civil engineering works)

Harmonised standard: EN 1504-5:2004

Notified body: Karlsruher Institut für Technologie (KIT),
0754-CPR-15-0412

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Adhesion	> 3 N/mm ²	EN 1504-5:2004
Volumetric shrinkage	NPD	
Glass transition temperature	> 40 °C	
Injectability into dry medium	Class 0.1 (0.1 mm)	
Injectability into nondry medium	Class 0.1 (0.1 mm)	
Durability (Compatibility with concrete)	Fulfilled	
Release of dangerous substances	EN 1504-5, Art. 5.4	

a) Pursuant to Commission Decision 2010/85 / EU of 09.02.2010, the product complies with fire classification E, without that an examination is required.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John van Diemen
Head of research and development and quality control



Bottrop, 15.05.2019
(place and date of issue)

.....
(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.