DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Reference number of the declaration of performance	: IN4404015_20170817			
Unique identification code of the product-type: ombran MHP 15				
Intended use: Cementitious coating for structural and non-structural repair of sewage structures				
Applying mortar by hand (3.1)				
Manufacturer:	MC-Bauchemie Müller GmbH & Co.KG Am Kruppwald 1-8 46238 Bottrop			
System of AVCP:	System 2+ (for uses in buildings and civil engineering works)			
Harmonised standard:	EN 1504-3:2005			
Notified body:	Karlsruher Institut für Technologie (KIT) Materialprüfungs- und Forschungsanstalt, MPA Karlsruhe Identification no: 0754			

Declared performances:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength	class R3 (≥ 25 MPa)	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0.05 %		
Adhesive bond	≥ 1.5 MPa		
Restrained shrinkage/expansion	≥ 1.5 MPa		
Carbonation resistance	d _k ≤ reference concrete (MC(0,45))		
Elastic modulus	≥ 15 GPa		
Thermal compatibility: freeze-thaw	≥ 1.5 MPa		
Capillary absorption	≤ 0.5 kg⋅m ⁻² ⋅h ^{-0.5}		
Reaction to fire	class A1		
Dangerous substances	EN 1504-3, Pkt. 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Carsten Zilg Head of research and development and quality control



(signature)

Bottrop, 17.08.2017 (place and date of issue)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is attached to this Declaration of Performance.